


Product Information ISO Class 5-8 Cleanroom Class 100-100,000 EU Grade C-D

# Sunsorb<sup>®</sup> 450 Polyester Cellulose Blend Nonwoven Wiper

Sunsorb<sup>®</sup> 450 is polyester & cellulose nonwoven wiper recommended for ISO Class 5 and above environments.

This wiper is suitable for many cleaning applications and has a excellent choice for wiping delicate and fine surfaces. And best of all, it is economical to use



#### Key Attributes

- Nonwoven polyester & cellulose blend
- Quarter folded to enhance the caliper

## Benefits

- Excellent strength and durability
- Excellent sorbency and durable
- · Chemically compatible with common cleaning and disinfecting solutions
- Economical

## Environmental

- Complies with RoHS 2002/05 and REACH requirements
- Light weight, high absorbency design can reduce landfill waste impact when compared to more traditional heavier weight products

#### Applications

- Critical industrial applications where absorbency and softness are required
- · Cleaning of support/less critical areas and manufacturing processes in regulated environments
- · Wiping of optics and other sensitive surfaces
- Steam autoclavable for use in aseptic applications
- Compatible with ISO Class 5 (Class 100) cleanroom applications and above
- Other ISO Class 5 and above nonwoven wipers
- Durx<sup>®</sup> 670A
- Durx<sup>®</sup> 620A
- Durx<sup>®</sup> 670
- Durx<sup>®</sup> 770
- BlueSorb® 750
- Labx<sup>®</sup> 123
- Labx<sup>®</sup> 170
- Lensx<sup>®</sup> 90
- MicroFirst®
- MicroFirst<sup>®</sup> LP
- Pro-Wipe® 750
- Pro-Wipe® 880
- Pro-Wipe® 750
- ValuClean<sup>™</sup>
- Sunsorb® 300
- EcoClean<sup>™</sup> 35
- EcoClean™ 60

 www.berkshire.com
 Americas
 Tel 1 413 528 2602
 Fax 1 413 528 2614
 usa@berkshire.com

 Contact:
 Tel 65 6252 4313
 Europe
 Tel 44 (0) 870 757 2877
 Fax 44 (0) 870 757 2878
 enquiries@berkshire.uk.com

 Email:
 enquiries@berkshire.com.sg
 SE Asia
 Tel 65 6252 4313
 Fax 65 6252 4312
 enquiries@berkshire.com.sg

 Japan
 Tel 81 45 477 4481
 Fax 81 45 477 4484
 master@berkshire.co.jp



## Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m²	49	TAPPI T-410
Caliper		μm	309	TAPPI T-411
Fibers	<u>&gt;</u> 100µm	fibers/cm <sup>2</sup>	2.4	IEST-RP.CC004.3, Sec 6.1.4 / Sec 6.2.2
Particles	<u>&gt;</u> 0.5µm	x10 <sup>3</sup> /cm <sup>2</sup>		IEST-RP.CC004.3, Sec 6.1.4 / Sec 6.2.2
Sorbency	Capacity	mL/m	217	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	4.4	
	Rate	seconds	2	
Non-Volatile Residue	DI Water	g/m²	0.12	IEST-RP.CC004.3, Sec 7.1.2
	IPA	g/m²	0.12	
lons	Na⁺	ppm	240	IEST-RP.CC004.3, Sec 7.2.2
	K⁺	ppm	10.7	
	Ca++	ppm	12.4	
	Mg++	ppm	8.4	

## Notes:

- All values are statistical averages.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- Third party testing can be performed upon request.

# **Order Information**

Product	Number	Size	Shts/pk	Pks/cs	Style
Sunsorb® 450	SS450.0505.30	5x5" (13x13cm)	100	30	Quarter folded, Stacked Pack

Other sizes and custom sizes are also available upon request.

For more information on our other contamination control products or technical consultation, please contact your Berkshire Sales Representative or e-mail: enquiries@berkshire.com.sg.

