

Product Information ISO Class 5-8Cleanroom Class 100 - 100,000 EU Grade B/C/D

MicroFirst[®]

45% Cellulose / 55% Polyester Nonwoven Cleanroom Wiper

MicroFirst® is an apertured cellulose / polyester nonwoven This combination of properties provides MicroFirst® wiper recommended for ISO Class 5 and above environments composed of a hydroentangled nonwoven blend of 45% cellulose and 55% polyester.

with the level of absorbency, abrasion resistance and chemical compatibility required for controlled environments and applications where both cleanliness

45% cellulose / 55% polyester hydroentangled nonwoven blend

Apertured for increased absorbency to weight ratio

Low extractable levels and particle and fiber counts

Polishing and cleaning metals, plastics, epoxy surfaces

General purpose wiping applications and spill control

Chemically compatible with common cleaning and disinfecting solutions

Designed for use in ISO Class 5 and higher cleanroom environments

General wiping in component prep, compounding and wash areas

Applying and removing cleaning and disinfecting solutions

No binders or other chemical additives

Very durable with high wet strength

Key Attributes

.

Benefits

cellulose

Autoclavable Economical

Environmental

Applications

•

and economy are of the most importance.

- BlueSorb[®] 750

Pre-Wetted Option

The same wiper material can be provided in pre-wetted formats for reduced VOC emissions, increased convenience, increased productivity, improved solvent control and cleaning protocol repeatability and reduced costs.

· Excellent combination of the synthetic polyester strength and cleanliness with the absorbent characteristics of

Apertured for increased absorbency and increased surface texture for improved cleaning efficiency

Lightweight design helps reduce landfill waste impact compared to heavier weight nonwovens

Sterile Validated Option

Cleaning of lab equipment

For aseptic processing areas, the same wiper material can be provided in a gamma irradiated validated sterile to a 10⁻⁶ sterility assurance level. Dry and pre-wetted versions available.

www.berkshire.com.sq

Contact: Tel 65.6252.4313 / Fax: 65.6252.4312 Email:enquiries@berkshire.com.sg

America	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp

Other ISO Class 5 and above nonwoven wip-

- ers
- Durx[®] 670
- Durx[®] 770
- MicroFirst LP®
- ProjX[®] 700
- Pro-Wipe® 750 Pro-Wipe[®] 880
- ValuClean® Plus

BC_1130_08-2015



Technical Data:

Attribute		Units	Value	Test Method	
Basis Weight		g/m ²	56.3	TAPPI T-410	
Caliper		μm	248	TAPPI T-411	
Fibers	≥100µm	fibers/cm ²	89	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2	
Particles	≥0.5µm	x10 ³ /cm ²	8.5	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1	
Sorbency	Capacity	mL/m ²	256	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified	
	Efficiency	mL/g	4.5		
	Rate	seconds	3		
Non-Volatile Residue	DI Water	g/m ²	0.023	IEST-RP.CC004.3, Sec 7.1.2	
	IPA	g/m²	0.0044		
Ions	Na⁺	ppm	15	IEST-RP.CC004.3, Sec 7.2.2	
	K+	ppm	2.6		
	Ca++	ppm	18		
	Mg ⁺⁺	ppm	5.4		
	Cl-	ppm	12		

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as ٠ product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product • comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions Third party testing can be performed upon request •

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	Style
MicroFirst®	MF.0909.20	9x9" (23x23cm)	300	20	Stacked
MicroFirst®	MF.1212.20	12x12" (30x30cm)	150	20	Stacked

Other Berkshire Products



Mop Systems

Wipers



Face Masks





Swabs

Documentation Systems

Glove Liners

www.berkshire.com.sg

Contact: Tel 65.6252.4313 / Fax: 65.6252.4312 Email:enquiries@berkshire.com.sg BC_1130_08-2015