

Product Information ISO Class 5 — 8 Cleanroom Class 100 – 100,000

EU Grade A/B/C/D USP <797>

Gamma Wipe[®] 600

Sterile Polyester / Cellulose Nonwoven Wiper

Gamma Wipe[®]600 is a polyester / cellulose blend wiper recommended for ISO Class 5 and above environments composed of 50% polyester and 50% cellulose. Each package is gamma irradiated to a 10⁶ Sterility Assurance. This combination of properties provides Gamma Wipe[®] 600 with the level of cleanliness, abrasion resistance and chemical compatibility required for cleaning general sterile processing areas where both economy and cleanliness are required.



Other Sterile wipers

- Gamma Wipe SuperSorb®
- Gamma Wipe[®] 300
- Gamma Wipe[®] 120
- Gamma Wipe[®] 67

Key Attributes

- 50% cellulose / 50% polyester hydroentangled nonwoven
- No secondary binders
- Available in 12x12"
- Gamma irradiated and sterile validated to a 10⁻⁶ Sterility Assurance Level per AAMI guidelines
- Header style packaging with Package Integrity testing
- Lot number on each pack
- Certificate of Sterility with each case is available. Details: Expiration Date, Radiation Dosage, Lot Information, Meets cGMP requirements for traceability

Benefits

- Excellent combination of the synthetic polyester strength and cleanliness with the absorbent characteristics of cellulose.
- Smooth, highly absorbent and durable with low extractable levels
- Economical
- Chemically compatible with common cleaning and disinfecting solutions including isopropyl alcohol, phenols, bleaches and quarternary ammonium compounds

Applications

- Designed for use in ISO Class 5 and higher sterile environments and USP <797> applications
- Designed for cleaning sterile surfaces and equipment during aseptic processing
- General wiping in component prep, compounding and wash areas
- General wipedowns in sterile gowning rooms
- Applying and removing cleaning and disinfecting solutions

Pre-Wetted Option

The same wiper material can be provided in pre-wetted formats for reduced VOC emissions, increased convenience, increased productivity, improved solvent control and cleaning protocol repeatability and reduced costs. Pre-wetted options include WFI.

Validated Sterile

ANSI/AAMI/ISO procedures have been followed for verification of irradiation dose with audits being performed to monitor bioburden levels and dose. The Sterility Assurance Level (SAL) or the probability of a viable organism being present on a product unit after sterilization is a SAL of 10⁻⁶ (which is the chance of 1 non-sterile unit in 1,000,000).

www.berkshire.com Contact: Tel 1 800 242 7000 / 1 413 528 2602 info@berkshire.com	America	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
	Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
	SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
	Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data:

Attribute		Units	Value	Test Method	
Basis Weight		g/m ²	60.7	TAPPI T-410	
Caliper		μm	289	TAPPI T-411	
Fibers	<u>></u> 100µm	fibers/cm ²	90	IEST-RP.CC004.3, Sec 6.1.4 / Sec 6.2.2	
Particles	<u>></u> 0.5µm	x10 ³ /cm ²	5.2	IEST-RP.CC004.3, Sec 6.1.4 / Sec 6.2.1	
Sorbency	Capacity	mL/m²	285	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified	
	Efficiency	mL/g	4.7		
	Rate	seconds	3		
Non-Volatile Residue	DI Water	g/m²	0.025	IEST-RP.CC004.3, Sec 7.1.2	
	IPA	g/m²	0.0054		
Ions	Na⁺	ppm	37	IEST-RP.CC004.3, Sec 7.2.2	
	K+	ppm	9.6		
	Ca++	ppm	13		
	Mg ⁺⁺	ppm	1.8		
	CI	ppm	26		

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as
 product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product

Order Information:

- - -

Product	Number	Size	Shts/pk	Pks/cs	Style
Gamma Wipe [®] 600	GW600AST25	12x12"(30x30cm)	20	25	Header Bag



www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602 / info@berkshire.com BC_3060_10-2017