

Product Information

ISO Class 3-5

Cleanroom Class 1 - 100 EU Grade B/C/D

MicroSeal® LI

Sealed Edge Cleanroom Laundered 100% Polyester Knit Wiper

MicroSeal® LI is a ultrasonically sealed edge cleanroom laundered wiper recommended for ISO Class 3 and above environments. Composed of 100% polyester continuous filament yarns, its smooth knit construction and ultrasonic NVR and ionic contaminant levels, making MicroSeal® LI sealed edges make it deal for applications requiring

critically low levels of particle and fiber release along with durability and chemical compatibility. A proprietary ISO Class 4 cleanroom laundry process helps ensures ultra low suitable for the most sensitive cleaning processes.



Key Attributes

- 100% continuous filament polyester knit
- Ultrasonically sealed edges provide low fiber release
- Laundered and packaged in an ISO Class 4 cleanroom

Benefits

- Critically low particles, fibers, ions and extractables
- Chemically compatible with IPA, Acetone and other solvents
- Steam autoclavable

Applications

- Designed for use in ISO Class 3 and higher cleanroom environments
- Designed for the highest level of contamination control in critical processing applications
- Chamber cleaning and CMP processing
- Stencil and other print roll cleaning applications
- Steam autoclavable for aseptic applications
- Cleaning of medical device products
- Applying and removing cleaning and disinfecting solutions

Other ISO Class 3 and above wipers

- MicroSeal SuperSorb®
- MicroSeal SuperSorb® Lite
- UltraSeal® 3000
- MicroSeal® 1200
- MicroSeal® VP ValuSeal® LP
- ValuSeal® IonX®

www.berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877

America	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m²	141	TAPPI T410
Caliper		μm	594	ASTM D1777
Fibers	<u>≥</u> 100μm	_fibers/cm²	0.077	IEST-RP-CC004.3, Sec 6.1.4 / Sec 6.2.2
Particles	<u>≥</u> 0.5μm	x10³/cm²	0.99	IEST-RP-CC004.3, Sec 6.1.4 / Sec 6.2.1
Sorbency	Capacity	mL/m²	436	IEST-RP-CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	3.1	
	Rate	seconds	1.0	
Non-Volatile Residue	DI Water	g/m²	0.0049	IEST-RP-C004.3, Sec 7.1.2
	IPA	_g/m²	0.011	
Ions	Na ⁺	ppm	0.015	IEST-RP-CC004.3, Sec 7.2.2
	K ⁺	ppm	0.0040	
	Ca ⁺⁺	ppm	0.011	
	Mg**	ppm	0.00021	
	Cl ⁻	ppm	0.0059	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	Style
MicroSeal® LI®	MSLI090910	9x9" (23x23cm)	150	10	Stacked

Other Berkshire Products



Wipers



Glove Liners



Mop Systems



Documentation Systems



Face Masks



Swabs